

(NASA-TM-108682) TABLE OF NACA
WIND TUNNELS: BRIEF DESCRIPTION OF
NUMBERS 1 AND 2, 7 BY 10 FOOT AAL
WIND TUNNEL (NASA) 3 p

N93-72280

Unclas

29/02 0151427

ORIGINAL PAGE IS
OF POOR QUALITY

5341
AAL/1

TABLE OF NACA (AAL) WIND TUNNELS

Symbol	Laboratory	Test section size and shape	Speed (m.p.h.)	Density and type	Type of work and measuring apparatus
7x10 No.1	7- by 10-foot Wind Tunnel	7'x10' rectangular	300	Atmospheric, closed throat, 2- and 3-dimensional	Determination of lift, drag, and stability characteristics of complete models. Also drag and interference effects of component parts. Two-dimensional studies and development using a semi-or partial-span model. Tail surface studies and development using semi-span models and floor of the tunnel as a reflection plane. Six-component balance system. 200 kw, 400 cycle variable-frequency power for driving model propellers.
7x10 No.2	7- by 10-foot Wind Tunnel	7'x10' rectangular	300	Atmospheric, closed throat, 3-dimensional	Determination of lift, drag, and stability characteristics of complete models. Also drag and interference effects of component parts. Six-component balance system. 200 kw, 400 cycle variable-frequency power for driving model propellers.

FILE COPY

To be returned to the Files of
National Aeronautical Laboratory
National Advisory Committee
for Aeronautics

Symbol	Laboratory	Test section size and shape	Speed (m.p.h.)	Density and type	Type of work and measuring apparatus
16'H.S.T.	16-foot High-Speed Tunnel	16' diam. circular	600	Atmospheric, closed throat, 2- and 3-dimensional	Tests at high Reynolds number and high Mach number on large models of airplanes and on full-scale parts of airplanes, including propellers to determine performance stability and propeller efficiency. Investigation of compressibility effects by means of force measurements, boundary layer measurements, and wake surveys. Six-component balance system. 2000 hp, 120 cycle and 200 kw, 400 cycle variable-frequency power supply for model and full-scale propeller tests.